


DESCRIPTION

The UCAN Hollow Wall anchor is a light duty screw type expansion anchor designed specifically for fastening to cavity walls, constructed of drywall, plaster or wallboard. It is available in 1/8" to 1/4" screw sizes.

Once installed, the anchor creates a bearing surface with expanded arms guaranteeing a secure and reliable fixture.

This anchor comes complete with a combination head for both Robertson and slot screw drivers. It is also available in 1/8" size as a drive type which does not require a predrilled hole.

The MWA installation tool is available for easy one step expansion of the anchor. This tool eliminates the need to expand the anchor with a screw driver.




FEATURES

- One piece unit for fast installation
- Can be installed with a hollow wall anchor installation tool or a screw driver
- Drive type does not require predrilled hole
- Zinc plated

TYPICAL APPLICATIONS

- Fastening into hollow material
- Light loading applications
- Fastening into panel-boards
- Light shelving



ANCHOR SELECTION

Combination Head Screw Type

Part No.	Size	Board Thickness (Grip Range)	Drill Bit
	inch	inch	inch
MWA 18XS	1/8 XS	0 - 1/2	5/16
MWA 18S	1/8 S	1/8 - 1/2	5/16
MWA 18SL	1/8 SL	1/8 - 3/4	5/16
MWA 18L	1/8 L	5/8 - 7/8	5/16
MWA 316S	3/16 S	1/8 - 5/8	7/16
MWA 316L	3/16 L	5/8 - 1-1/4	7/16
MWA 14S	1/4 S	1/8 - 5/8	1/2
MWA 14L	1/4 L	5/8 - 1-1/4	1/2

Drive Type

Part No.	Size	Board Thickness (Grip Range)
	inch	inch
MWD 18S	1/8 S	1/8 - 1/2
MWD 18SL	1/8 SL	1/8 - 3/4
MWD 18L	1/8 L	1/8 - 3/4